SAFETY DATA SHEET



Lysol Brand Disinfectant Concentrate

1. Product and company identification

Product name Distributed by Lysol Brand Disinfectant Concentrate

Reckitt Benckiser LLC.

Morris Corporate Center IV

399 Interpace Parkway (P.O. Box 225) Parsippany, New Jersey 07054-0225

+1 973 404 2600

Emergency telephone number (Medical)

: 1-800-338-6167

Emergency telephone number (Transport)

: 1-800-424-9300 (U.S. & Canada) CHEMTREC

Outside U.S. and Canada (North America), call Chemtrec:703-527-3887

Website:

http://www.rbnainfo.com

: Disinfectant. **Product use**

This SDS is designed for workplace employees, emergency personnel and for other conditions and situations where there is greater potential for large-scale or prolonged exposure, in accordance with the requirements of **USDOL** Occupational Safety and Health Administration.

This SDS is not applicable for consumer use of our products. For consumer use, all precautionary and first aid language is provided on the product label in accordance with the applicable government regulations, and shown in Section 15 of this SDS.

SDS# : 353773PSDS v3.0 Formulation #: : 269-005 (353773 v10.0)

EPA ID No. 777-94

UPC Code / Sizes : 19200-02201-10; 19200-77500-10 (12 fl.oz. PET Amber Pour Bottle with CRC cap)

2. Hazards identification

Classification of the substance or mixture : FLAMMABLE LIQUIDS - Category 4 SKIN CORROSION/IRRITATION - Category 1C SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 Most Pangerous

OSHA Categories

GHS label elements

Hazard pictograms



Pangerous Product

Signal word

Hazard statements

Danger

Combustible liquid.

Causes severe skin burns and eye damage

Precautionary statements

Code # SDS# : 353773PSDS v3.0 Date of issue : 01/04/2015. 1/16 : FF353773

2. Hazards identification

Genera

Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

Prevention

: Wear protective gloves. Wear eye or face protection. Wear protective clothing. Keep away from flames and hot surfaces. - No smoking. Wash hands thoroughly after handling.

Response

POISON

: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or physician. IF SWALLOWED: Immediately call a POISON CENTER or physician. Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Wash contaminated clothing before reuse. Immediately call a POISON CENTER or physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Storage

: Store looked up. Store in a well-ventilated place. Keep cool.

Disposal

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

Supplemental label elements

: None known.

Hazards not otherwise

: None known.

classified

3. Composition/information on ingredients

Substance/mixture : Mixture

| Ingredient name | % | CAS number |
|---------------------|---------|------------|
| clorofene | 5 - 10 | 120-32-1 |
| potassium hydroxide | 2.5 - 5 | 1310-58-3 |
| Ethyl alcohol | 1 - 2.5 | 64-17-5 |
| Isopropyl alcohol | 1 - 2.5 | 67-63-0 |

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First aid measures

Description of necessary first aid measures

Eye contact

eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promotly by a physician.

Inhalation

Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

4. First aid measures

Skin contact

Get medical attention immediately. Call a poison center or physician. Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. Wash clothing before reuse.

Ingestion

This is a poison!

Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove denturce if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Acute health

effects

Most important symptoms/errects, acute and delayed

Potential acute health effects

Eye contact : Causes serious eye damage.

Inhalation : May give off gas, vapor or dust that is very irritating or corrosive to the respiratory

system.

Skin contact : Causes severe burns.

ingestion: May cause burns to mouth, throat and stomach.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:

pain watering redness

Inhalation : No specific data.

Skin contact: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur

Ingestion: Adverse symptoms may include the following:

stomach pains

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it is

suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water

before removing it, or wear gloves.

See toxicological information (Section 11)

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

: Use dry chemical, CO2, water spray (fog) or foam.

Unsuitable extinguishing

: Do not use water jet.

metal oxide/oxides

Specific hazards arising from the chemical

Combustible liquid. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard.

Hazardous thermal decomposition products

: Decomposition products may include the following materials: carbon dioxide carbon monoxide halogenated compounds

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders:

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

6. Accidental release measures

Clean-up Protocols
- remain upwind
- spark-proof tools
- keep from sewers

Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

7. Handling and storage

Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment see Section 8). Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous. Do not reuse container.

Conditions for safe storage, : including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

8. Exposure controls/personal protection

Control

Occupational exposure limits

| Ingredient name | Inc | ired | ient | name | |
|-----------------|-----|------|------|------|--|
|-----------------|-----|------|------|------|--|

potassium hydroxide

Ethyl alcohol

Exposure limits

ACGIH TLV (United States, 6/2013).

C: 2 mg/m³

OSHA PEL 1989 (United States, 3/1989).

CEIL: 2 mg/m³

NIOSH REL (United States, 10/2013).

TWA: 2 mg/m³ 10 hours.

ACGIH TLV (United States, 6/2013).

STEL: 1000 ppm 15 minutes.

OSHA PEL 1989 (United States, 3/1989).

TWA: 1000 ppm 8 hours. TWA: 1900 mg/m³ 8 hours.

NIOSH REL (United States, 10/2013).

TWA: 1000 ppm 10 hours. TWA: 1900 mg/m³ 10 hours. OSHA PEL (United States, 2/2013).

8. Exposure controls/personal protection

TWA: 1900 mg/m³ 8 hours.

Isopropyl alcohol ACGIH TLV (United States, 6/2013).

TWA: 200 ppm 8 hours. STEL: 400 ppm 15 minutes.

TWA: 1000 ppm 8 hours.

OSHA PEL 1989 (United States, 3/1989).

TWA: 400 ppm 8 hours.
TWA: 980 mg/m³ 8 hours.
STEL: 500 ppm 15 minutes.
STEL: 1225 mg/m³ 15 minutes.
NIOSH REL (United States, 10/2013).

TWA: 400 ppm 10 hours. TWA: 980 mg/m³ 10 hours. STEL: 500 ppm 15 minutes. STEL: 1225 mg/m³ 15 minutes. OSHA PEL (United States, 2/2013).

TWA: 400 ppm 8 hours. TWA: 980 mg/m³ 8 hours.

Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

8. Exposure controls/personal protection

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Extreme personal protection

9. Physical and chemical properties

Appearance

Physical state : Liquid. [Clear.]

Color : Red.

Odor : soap

Odor threshold : Not available.

PH : 10.3 to 11.1 [Conc. (% w/w): 100%]

Melting point: Not available.Boiling point: Not available.

Flash point : Closed cup: 62.8°C (145°F)

Evaporation rate : Not available.
Flammability (solid, gas) : Not available.
Lower and upper explosive : Not available.

(flammable) limits

Vapor pressure : Not available.
Vapor density : Not available.
Relative density : 1.024 to 1.034

Solubility : Easily soluble in the following materials: cold water and hot water.

Partition coefficient: n-

octanol/water

: Not available.

Auto-ignition temperature : Not available.

Decomposition temperature : Not available.

Viscosity : Not available.

10. Stability and reactivity

Reactivity

: No specific test data related to reactivity available for this product or its ingredients.

Chemical stability

: The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid

: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

Incompatible materials

: Reactive or incompatible with the following materials:

oxidizing materials

Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11. Toxicological information

Information on toxicological effects

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|-----------------------------|-----------------------|---------|--------------------------|----------|
| clorofene | LD50 Oral | Rat | 1700 mg/kg | - |
| Ethyl alcohol | LC50 Inhalation Vapor | Rat | 124700 mg/m ³ | 4 hours |
| | LD50 Oral | Rat | 7 g/kg | - |
| Isopropyl alcohol | LD50 Dermal | Rabbit | 12800 mg/kg | - |
| | LD50 Oral | Rat | 5000 mg/kg | - |
| *Lysol Brand Disinfectant | LC50 Inhalation Vapor | Rat | >2.07 mg/l | 4 hours |
| Concentrate, Original Scent | | | | |
| _ | LD50 Dermal | Rabbit | >5000 mg/kg | - |
| | LD50 Oral | Rat | 5000 mg/kg | - |

Conclusion/Summary

: Not classified Harmful. *Information is based on toxicity test result of a similar product.

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|--|--|------------------|-------|----------------|-------------|
| clorofene | Skin - Mild irritant | Human | - | 48 hours 1 | - |
| | | | | Percent | |
| potassium hydroxide | Eyes - Moderate irritant | Rabbit | - | 24 hours 1 | - |
| | | | | milligrams | |
| | Skin - Severe irritant | Guinea pig | - | 24 hours 50 | - |
| | | | | milligrams | |
| | Skin - Severe irritant | Human | - | 24 hours 50 | - |
| | | | | milligrams | |
| | Skin - Severe irritant | Rabbit | - | 24 hours 50 | - |
| | | | | milligrams | |
| Ethyl alcohol | Eyes - Moderate irritant | Rabbit | - | 0.06666667 | - |
| | | | | minutes 100 | |
| | | | | milligrams | |
| | Eyes - Mild irritant | Rabbit | - | 24 hours 500 | - |
| | | D 11.7 | | milligrams | |
| | Eyes - Moderate irritant | Rabbit | - | 100 | - |
| | E O i . it i | D. I. I. I | | microliters | |
| | Eyes - Severe irritant | Rabbit | - | 500 milligrams | |
| | Skin - Mild irritant | Rabbit | - | 400 milligrams | - |
| | Skin - Moderate irritant | Rabbit | - | 24 hours 20 | - |
| la annound ala ala al | Free Madagata instant | Dabbit | | milligrams | |
| Isopropyl alcohol | Eyes - Moderate irritant | Rabbit | - | 24 hours 100 | - |
| | Cues Madarata invitant | Dabbit | | milligrams | |
| | Eyes - Moderate irritant | Rabbit Rabbit | - | 10 milligrams | - |
| | Eyes - Severe irritant Skin - Mild irritant | Rabbit | - | 100 milligrams | |
| *Lycal Brand Disinfortant | | | - | 500 milligrams | |
| *Lysol Brand Disinfectant Concentrate, Original Scent | Skin - Visible necrosis | Rabbit | - | 240 minutes | 14 days |
| Concentrate, Original Scent | Eyes - Cornea opacity | Rabbit | >3 | | |
| | Lyes - Comea upacity | | -3 | _ | - |

Conclusion/Summary

Skin

: Causes burns. *Information is based on toxicity test result of a similar product.

Eyes

: Causes irreversible eye damage *Information is based on toxicity test result of a similar product.

Sensitization

11. Toxicological information

| 3 | Route of exposure | Species | Result |
|--|-------------------|------------|-----------------|
| *Lysol Brand Disinfectant Concentrate, Original Scent | skin | Guinea pig | Not sensitizing |

Conclusion/Summary

Skin : Non-sensitizer to skin. *Information is based on toxicity test result of a similar product.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

| Product/ingredient name | OSHA | IARC | NTP |
|-------------------------|------|------|-----|
| Ethyl alcohol | - | 1 | - |
| Isopropyl alcohol | - | 3 | - |

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

| Name | | Route of exposure | Target organs |
|-------------------|------------|-------------------|------------------|
| Isopropyl alcohol | Category 3 | Not applicable. | Narcotic effects |

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely routes of exposure

: Not available.

Potential acute health effects

Eye contact

Inhalation

Causes serious eye damage.

May give off gas, vapor or dust that is very irritating or corrosive to the respiratory

Skin contact : Causes severe burns.

Ingestion : May cause burns to mouth, throat and stomach.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact: Adverse symptoms may include the following:

pain watering redness

11. Toxicological information

Inhalation

Skin contact

: No specific data.

Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur

Ingestion

Adverse symptoms may include the following: stomach pains

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate

effects

: Not available.

Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General No known significant effects or critical hazards. : No known significant effects or critical hazards. Carcinogenicity **Mutagenicity** : No known significant effects or critical hazards. : No known significant effects or critical hazards. **Teratogenicity Developmental effects** : No known significant effects or critical hazards. **Fertility effects** : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Not available.

12. Ecological information

Toxicity

| Product/ingredient name | Result | Species | Exposure |
|-------------------------|--------------------------------------|---------------------------------|----------|
| clorofene | Acute EC50 0.59 ppm Fresh water | Daphnia - Daphnia magna | 48 hours |
| | Acute LC50 0.33 ppm Fresh water | Fish - Lepomis macrochirus | 96 hours |
| potassium hydroxide | Acute LC50 80 ppm Fresh water | Fish - Gambusia affinis - Adult | 96 hours |
| Ethyl alcohol | Acute EC50 17.921 mg/l Marine water | Algae - Ulva pertusa | 96 hours |
| • | Acute EC50 2000 µg/l Fresh water | Daphnia - Daphnia magna | 48 hours |
| | Acute LC50 25500 µg/l Marine water | Crustaceans - Artemia | 48 hours |
| | | franciscana - Larvae | |
| | Acute LC50 42000 µg/l Fresh water | Fish - Oncorhynchus mykiss | 4 days |
| | Chronic NOEC 4.995 mg/l Marine water | Algae - Ulva pertusa | 96 hours |
| | Chronic NOEC 0.375 ul/L Fresh water | Fish - Gambusia holbrooki - | 12 weeks |
| Code # : FF353773 | SDS # : 353773PSDS v3.0 | Date of issue : 01/04/2015. | 10/16 |

12. Ecological information

| | | Larvae | |
|-------------------|--------------------------------------|-------------------------------|----------|
| Isopropyl alcohol | Acute LC50 1400000 µg/l Marine water | Crustaceans - Crangon crangon | 48 hours |
| | Acute LC50 4200 mg/l Fresh water | Fish - Rasbora heteromorpha | 96 hours |

Persistence and degradability

Not available.

BAD FOR THE ENVIRONMENT

Bioaccumulative potential

| roduct/ingredient name | LogP _{ow} | BCF | Potential |
|------------------------|--------------------|-----|-----------|
| clorofene | 3.6 | - | low |
| Ethyl alcohol | -0.35 | - | low |
| Isopropyl alcohol | 0.05 | - | low |

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

14. Transport information

| Regulatory information | UN number | Proper shipping name | Classes | PG* | Label | Additional information |
|------------------------|-----------|----------------------|---------|-----|-------|------------------------|
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |

Code # : FF353773 (353773PSDS) **SDS** # : 353773PSDS v3.0 **Date of issue** : 01/04/2015.

11/16

14. Transport information

| DOT Classification | UN1760 | Corrosive liquids, n.o. s. (potassium | 8 | II | | Reportable quantity 25990.9 lbs / 11799.9 |
|--------------------------|--------|---|---|----|-------------|---|
| | | hydroxide, 2,4-xylenol) RQ (potassium | | | CORROSIVE 8 | kg [3029.3 gal / 11467. 3 L] |
| | | hydroxide, 2,4-xylenol) | | | | Package sizes shipped in quantities |
| | | | | | | less than the product reportable quantity are not subject to the RQ |
| | | | | | | (reportable quantity) transportation |
| | | | | | | requirements. |
| | | | | | | Limited quantity Yes. |
| | | | | | | Packaging instruction |
| | | | | | | Passenger aircraft Quantity limitation: 1 L |
| | | | | | | Cargo aircraft Quantity limitation: 30 |
| | | | | | | L |
| | | | | | | Special provisions B2, IB2, T11, TP2, TP27 |
| TDG Classification | UN1760 | CORROSIVE LIQUID, N.O.S. (potassium | 8 | II | | Explosive Limit and Limited Quantity |
| | | hydroxide, 2,4-xylenol) | | | 8 | Index 1 |
| | | | | | | Passenger Carrying Road or Rail Index |
| | | | | | | 1 |
| | | | | | | Special provisions 16 |
| Mexico Classification | UN1760 | LIQUIDO CORROSIVO, N.E.P. | 8 | II | | Special provisions 274 |
| | | (potassium hydroxide, 2,4-xylenol) | | | 8 | |
| IMDG Class | UN1760 | CORROSIVE LIQUID, N.O.S. (potassium hydroxide, 2,4-xylenol) | 8 | II | | Emergency schedules (EmS) F-A, S-B |
| | | | | | Ť | Special provisions 274 |
| | | | | | | |
| | | | | | | |

14. Transport information

| | | |
|---|--|-----------------|
| IATA-DGR Class UN1760 Corrosive liquid, n.o.s (potassium hydroxide 2,4-xylenol) | Quar Pack 851 Carg Quar L Pack 855 Limi Pass Quar L Pack Y840 | cial provisions |

PG*: Packing group

15. Regulatory information

U.S. Federal regulations : TSCA 8(a) PAIR: 2-methylpropan-2-ol

TSCA 8(a) CDR Exempt/Partial exemption: Not determined

United States inventory (TSCA 8b): Not determined. Clean Water Act (CWA) 307: clorofene; 2,4-xylenol

Clean Water Act (CWA) 311: potassium hydroxide; sodium hydroxide; ammonia,

anhydrous; xylenol; m-cresol; p-cresol

Clean Air Act Section 112

(b) Hazardous Air **Pollutants (HAPs)** : Not listed

Clean Air Act Section 602

Class I Substances

: Not listed

Clean Air Act Section 602

Class II Substances

: Not listed

DEA List I Chemicals

(Precursor Chemicals)

: Not listed

DEA List II Chemicals

: Not listed

(Essential Chemicals)

SARA 302/304

Composition/information on ingredients

| | | | SARA 302 TPQ | | SARA 304 RQ | |
|---------|--------|------|--------------|-----------|-------------|-----------|
| Name | % | EHS | (lbs) | (gallons) | (lbs) | (gallons) |
| Ammonia | < 0.01 | Yes. | 500 | - | 100 | - |

SARA 304 RQ : 100000000 lbs / 45400000 kg [11655404.4 gal / 44120505.3 L]

Code # : FF353773 SDS# : 353773PSDS v3.0 **Date of issue** : 01/04/2015. 13/16

15. Regulatory information

SARA 311/312

Classification

: Fire hazard

Immediate (acute) health hazard

Composition/information on incredients

| Name | % | hazard | Sudden release of pressure | | Immediate (acute) health hazard | Delayed (chronic) health hazard |
|--|---------|----------------------------|----------------------------------|--------------------------|--|--|
| clorofene potassium hydroxide Ethyl alcohol Isopropyl alcohol | 2.5 - 5 | No. No. Yes. Yes. | No. No. | No. No. No. No. | Yes. Yes. Yes. Yes. | No. No. No. No. |

SARA 313

| | Product name | CAS number | % |
|---------------------------------|-------------------|------------|--------|
| Form R - Reporting requirements | clorofene | 120-32-1 | 5.4998 |
| | Isopropyl alcohol | 67-63-0 | 1.8333 |
| Supplier notification | clorofene | 120-32-1 | 5.4998 |
| | Isopropyl alcohol | 67-63-0 | 1.8333 |

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts

: The following components are listed: POTASSIUM HYDROXIDE; ISOPROPYL

ALCOHOL; ETHYL ALCOHOL

New York

: The following components are listed: Potassium hydroxide

New Jersey

: The following components are listed: POTASSIUM HYDROXIDE; CAUSTIC POTASH;

ISOPROPYL ALCOHOL; 2-PROPANOL; ETHYL ALCOHOL; ALCOHOL

Pennsylvania

: The following components are listed: POTASSIUM HYDROXIDE (K(OH)); CHLORINATED PHENOLS; 2-PROPANOL; DENATURED ALCOHOL

Label elements

Signal word: : DANGER

Hazard statements : Harmful if swallowed.

Corrosive Causes irreversible eye damage

Corrosive CAUSES SKIN BURNS.

Precautionary measures

Keep out of reach of children.

Do not get in eyes, on skin, or on clothing.

Avoid breathing vapor or mist.

Wear protective gloves/protective clothing/eye protection/face protection.


Wash thoroughly with soap and water after handling and before eating, drinking, chewing

gum, using tobacco or using the toilet.

Remove contaminated clothing and wash it before reuse.

Avoid breathing dust/fume/gas/mist/vapors/spray.

16. Other information



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910. 1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Key to abbreviations : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations

Date of issue : 01/04/2015.

Date of previous issue : 09/04/2010.

Version : 3

16. Other information

Prepared by : Reckitt Benckiser LLC.

Product Safety Department

1 Philips Parkway

Montvale, New Jersey 07646-1810 USA.

FAX: 201-476-7770

Revision comments : Update as per US GHS.

▼ Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.



RB is a member of the CSPA Product Care Product Stewardship Program.